

## 4MP Fixed Dome Network Camera

### CC-124R3-P28



#### Key Features

##### Optics

- Day/night functionality
- SmartIR, up to 30 m (98 ft) IR distance
- Car-grade LEDs, brighter and uniform light compensation
- 3D DNR (Digital Noise Reduction)

##### Compression

- H.265, H.264, MJPEG
- Triple streams
- ROI (Region of Interest)
- Customized OSD

##### Network

- ONVIF Conformance

##### Structure

- Wide temperature range: -30°C to 60°C (-22°F to 140°F)
- Wide input voltage range of  $\pm 25\%$
- 2-Axis
- IK10 vandal resistant

- IP66

## Specifications

	CC-124R3-P28
<b>Camera</b>	
Sensor	1/3", 4 megapixel, progressive scan CMOS
Lens	2.8 mm@F2.2
Angle of View (H)	105.2°
Shutter	Auto/Manual, 1/6~1/100000 s
Min. Illumination	Colour: 0.2 Lux (F2.2, AGC ON) 0 Lux with IR
Day/Night	IR-cut filter with auto switch (ICR)
S/N	>52dB
WDR	Digital
Noise Reduction	2D/3D
<b>Video</b>	
Max. Resolution	2592 × 1520
Video Compression	H.265, H.264, MJPEG
Frame Rate	4MP (2592 × 1520): Max. 20 fps; 4MP (2560 × 1440): Max. 25 fps 3MP (2048 × 1520): Max. 30 fps; 1080P (1920 × 1080): Max. 30 fps
Video Streaming	Triple
9:16 Corridor Mode	Supported
ROI	Supported
HLC	Supported
Evaluative Metering	Supported
OSD	Up to 8 OSDs
Motion Detection	Up to 4 areas
Privacy Mask	Up to 8 areas
<b>Network</b>	
Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SIP, 802.1x
Compatible Integration	ONVIF, API
<b>Interface</b>	
Network	10M/100M Base-TX Ethernet
<b>General</b>	
Power	12 V DC, or PoE (IEEE802.3 af) Power consumption: Max 5.0W
Dimensions (Ø x H)	Φ108.5 x 81 mm (Ø4.28" x 3.2")
Weight	0.3 kg (0.66 lb)
Working Environment	-30°C ~ +60°C (-22°F ~ 140°F), Humidity ≤ 95% RH(non-condensing)
Ingress Protection	IP66

Dimensions

