

# COEX™ C2000-1F HD IP Camera Station

The COEX™ C2000-1F HD IP camera series has a unique compact & lightweight design specifically developed for industrial and marine applications. With a 316L stainless steel enclosure the C2000-F is designed for toughness and durability to operate in the most adverse environments – from extremely low temperatures where ice is prevalent to severe weather conditions on all types of vessels.



The C2000 HD IP incorporates a 1080P HD video camera module with 30x optical zoom for outstanding image quality. The unit is designed to stream video in ambient temperatures of up to +70°C.

Fully controllable via Synergy, configurable and upgradable through an in-built web server providing remote access to maintenance staff and operators to ensure optimum operability and reliability.

The COEX™ C2000 camera stations can operate in the most extreme environments and are certified for temperatures as low as -55°C to desert conditions of +70°C ambient temperature.

## Features

- DNV Type Approved
- EAC-TR CU Certified
- IP66 & IP67 Rated – Completely Protected Against Dust & Water Ingress, for the Most Demanding Environment
- Electro-polished 316L Stainless Steel, for Optimum Corrosion Resistance
- Native IP H.264 Encoding
- Low Voltage Operation
- In-built Web Server Allows Easy Configuration and Diagnostics

## Options

- Integral Wiper [W]
- COEX™ 'MEWS' Wash System
- Fibre Optic Available with Associated Junction Box

# Specifications

CERTIFICATIONS / RATINGS		[OPTIONS]
Certifications / Ratings	DNV Type Approval EAC-TR CU Certified EMC:61000 CE Compliant IP66 & IP67 to IEC 60529 Machinery Directive: 2006/42/EC LVD Directive: 2006/95/EC	
ENVIRONMENTAL		
Operating Temperature	-55°C to +70°C	
MECHANICAL		
Material	Electro-polished 316L Stainless Steel	
Window	Toughened Glass, Thermostatically Operated Demister [Wiper]	
Mounting	1 x Ø 10.5 mm	
Dimensions (W x D x H)	166 x 310 x 230 mm	
Weight* <sup>1</sup>	5 kg	
ELECTRICAL		
Power Requirements	24Vac 50 / 60Hz or 24Vdc (±10%)	
Power Consumption	20VA Maximum	
CAMERA / LENS		C2000-1F75 [W]
Image Sensor	1/2.8" Progressive Scan CMOS	
Signal System	HD: 1080p/29.97, 1080p/25	
Focus System	Auto, Manual, ICR-in Focus Compensation	
Exposure Control	AE Control: Auto, Manual	
Effective Pixels	Approximately 2.38 megapixels	
Electronic Shutter	1/1 to 1/10,000 sec, 22 steps	
S/N Ratio	>50dB	
Zoom Range	30x zoom Up to 12x digital zoom	
Minimum Illumination (50%, high sensitivity mode ON)	0.35 lux (shutter speed 1/30 sec) 0.05 lux (shutter speed ¼ sec, shutter speed ½ sec) ICR-ON mode: 0.013 lux (shutter speed 1/30 sec) 0.002 lux (shutter speed ¼ sec, shutter speed ½ sec, 30%) 1.4 lux (shutter speed 1/30 sec)	
Minimum Illumination (50%, high sensitivity mode OFF)	0.19 lux (shutter speed ¼ sec, shutter speed ½ sec) ICR-ON mode: 0.05 lux (shutter speed 1/30 sec)	
Iris	DC iris	
Focal Length	4.3 to 129 mm	
Aperture	F1.6 - 4.7	
Angle of View	63.7° to 2.3°	
CAMERA OPERATION		
Camera Functions	White Balance, WDR, Digital Zoom, Day / Night IR Cut Filter	
Wash**	24V switched output	
VIDEO COMPRESSION		
Compression	Selectable H.264 AVC High Profile / Main Profile (MPEG4 part 10)	
Output Streams	1 uni-cast stream or multi-cast	
Data Rate	Maximum 8Mb/s	
GOP Structure	Default 25/30	

**STREAMING OPTIONS**

Single Streaming Mode	H.264 1920x1080 (25/30fps)
Resolutions	H.264 - Full HD 1080P / qHD / WQVGA

**NETWORK**

Interface	RJ-45, 10/100 Mbps Ethernet
Protocol	RTP/RTSP, TCP/IP, UDP, IGMP, SNMP, HTTP, NTP
Password Levels	Administrator / User
Supported Internet Browsers	Chrome / Firefox / IE version 6 or higher

NOTE: \*1 Dependant on equipment fitted. \*2 Refer to Synectics for availability and compatibility with other control systems.

**Synectic Systems**  
[sales@synecticsglobal.com](mailto:sales@synecticsglobal.com)  
[synecticsglobal.com](http://synecticsglobal.com)

Specifications subject to change. E & OE.  
 Copyright © Synectic Systems Group Limited, Synectic Systems, Inc., Synectic Systems (Asia) Pte. Limited 2015. All Rights Reserved.

MANUFACTURER OF  
  
 CAMERA STATIONS

Reference Number:  
 C2000-1FHDIP/0215/A4 Iss 2