

DESKTOP BARCODE LABEL PRINTER

CL-S25IIB

- Thermal transfer and direct thermal printing
- High Resolution : 203DPI (8 dots/mm)
- Stable & reliable label printing
- High speed 127mm per second
- High capacity memory
- Large capacity of roll (200mm OD) with external media holder
- Less ribbon replacement with 360M length (Wax, Resin, Wax/Resin)
- Paper width adjustable from 18mm to 118mm
- Selectable optional Auto cutter or Peeler



INTERFACE



PEELER



AUTO CUTTER



SPECIFICATION

ITEM	TYPE
MODEL	CL-S25IIB
PRINT METHOD	Thermal Transfer and Direct Thermal
PRINTING SPEED	127 mm/sec
PRINT WIDTH	104mm (4.1")
PRINT LENGTH	1,000mm
RESOLUTION	203 DPI (8 dots/mm)
PAPER WIDTH	Min. 18mm ~ Max. 118mm (0.7" ~ 4.64")
PAPER ROLL SIZE (Min. ~ Max.)	Internal Ø 25.4 (1") ~ Ø 127mm (5.0") External Ø 38.1 (1.5") ~ Ø 200mm (7.8")
PAPER THICKNESS	0.06 ~ 0.20mm
PAPER TYPE	Label, Tag, Continuous, Fanfold
PAPER SENSOR	Label Gap Sensor, Black Mark Sensor, Notch Sensor
RIBBON WIDTH	Min. 33mm ~ Max. 110mm (1.3" ~ 4.3")
RIBBON LENGTH	360M, Ø 67mm (2.63")
MEMORY	Flash 1MB(in CPU), SDRAM 16MB, Serial Flash 8MB, EEPROM 2KB
BARCODE	1D Code39, Code128, with subsets A/B/C, Code93, Codabar, Interleaved 2 of 5, UPC-A and UPC-E with 2 or 5 digit extensions, EAN-8 and EAN-13 with 2 or 5 digit extensions, Postnet, Postnet, German Post Code, MSI-3, UCC/EAN-128 2D Artec, PDF 417, QR Code, Data matrix Code49
FONT SPECIFICATION	EPLII 8x12,10x16,12x20,14x24, 32x40 (5 Bitmap Font) - English, 24x24(KSC5601) - Korean ZPLII 5x9,7x11,10x18,15x28,13x26,40x60, 13x21 (7 Bitmap Font) 1 smooth scalable font
PROGRAMMING LANGUAGE	ZPLII, EPLII Command compatible
INTERFACE	STANDTAD USB + Serial(RS-232C) + Ethernet OPTIONAL Wi-Fi(802.11b), Bluetooth Ver4.2, RFID
POWER	AC100~240V, 24VDC, 2.5A
DIMENSIONS	215 x 287 x 231mm
WEIGHT(kg)	3.6kg
OPTION	Peeler, Auto Cutter, External Paper Supply

• All specification and designs are subject to change without notice.

