

5MP Starlight DarkHunter AHD Dome Camera

CC-HD514-ADF28M-WS



Key Features

- 5MP high quality imaging
- TVI/AHD/CVI/CVBS
- Supports White light illumination, 24/7 color images
- Supports 180° horizontal flip, 180° vertical flip
- OSD configuration menu, easy to operate
- IP66 waterproof and dustproof design, high reliability
- Built-in MIC
- Metal Case

Specifications

| | |
|------------------------------|---|
| | C-HD514-ADF28M-WS HD Camera |
| Sensor | |
| Pixel | 5.0 megapixel |
| Size | 1/2.8" |
| Min. Illumination | 0.005 lux (F1.2, AGC ON) 0 lux (white light on) |
| Lens | |
| Lens | 2.8mm@F1.2 |
| Lens mount | M12 |
| Angle of View (H) | 107° |
| Illuminator | |
| Illuminator | Two white-light illuminators |
| Illumination distance | 20~25m |
| Lifetime | ≥60,000 hours |
| Video | |
| Resolution | 2560(H) × 1920(V) |
| Frame rate | TVI/AHD/CVI: 5MP@20fps (default), 1080P@25-30fps; CVBS: PAL, NTSC |
| Shutter time | PAL: 1/25s-1/10000s NTSC: 1/30s-1/10000s |
| Image | |
| Exposure mode | Four modes: Global (default), BLC, HLC, DWDR |
| Day/Night | 24/7 color image |
| Digital noise reduction | 2D/3D |
| White balance | Two modes: Auto (default), Manual |
| WDR | DWDR |
| Flip | Supports 180° horizontal flip, 180° vertical flip |
| Audio | |
| Microphone | Built-in Mic |
| Interface | |
| Power | 5.5mm power interface |
| Video output | BNC, supports TVI/AHD/CVI/CVBS |
| Operating environment | |
| Temperature | -20°C to 55°C |
| Humidity | ≤95% (RH, non-condensing) |
| Ingress protection | IP66 |
| General | |
| Power | DC 12V (±25%), with reverse polarity protection. Max 3.12W |
| Material | Metal Case |
| Certification | CE |